

SUSPENSION	
Front	MacPherson strut with aluminum control arm and stabilizer bar; Continuously Controlled Damping (CCD)
Rear	Advanced multi-link suspension with Continuously Controlled Damping (CCD)
STEERING	
Type	Electric power assisted steering (EPAS)
Steering column	Manual tilt and telescoping
Ratio	14.8:1
Turns, lock-to-lock	2.7
Turning circle, curb-to-curb	38 ft.
BRAKES	
Type	Standard four-channel, four-wheel disc with Anti-lock Brake System (ABS); AdvanceTrac® ESC; Electric parking brake
Front	17-in. vented disc; rotors: 12.4 in. x 1.1 in.
Front swept area	500.7 sq. cm.
Rear	17-in. solid disc; rotors: 12.4 in. x .43 in.
Rear swept area	384.9 sq. cm.
WHEELS AND TIRES	
Wheel sizes and type	18-in. premium painted aluminum (standard)
	19-in. polished aluminum with painted pockets (optional)
	19-in. polished 18-spoke aluminum (optional)
	19-in. polished 10-spoke aluminum (late availability)
Tire size	P245/45R18
	P245/40R19
DIMENSIONS (inches unless otherwise noted)	
Exterior	
Wheelbase	112.2
Overall length	194.1
Overall width (excluding mirrors)	73.4
Overall width (including mirrors)	83.3
Overall height (without options)	58.2
Track width (front/rear)	62.3/62.0
Interior	
Seating capacity	Five
Headroom	
First row	37.9
Second row	36.6
Legroom	
First row (maximum)	44.3
Second row	37.0
Shoulder room	
First row	57.7
Second row	55.3
Hip room	
First row	55.1
Second row	53.8